

PRODUCT INFORMATION

ANGLER

ANGLER INDUSTRIES, INC.
61 Industrial Park Rd • PO Box 217
Sterling, CT 06377
860-564-0080 • FAX 860-564-3598

www.anglerindustries.com



AccuCool 3070

Ultra-Premium Metalworking Coolant Concentrate

DESCRIPTION

AccuCool 3070 represents the most up-to-date technology in the development of a semi-synthetic metalworking fluid. Formulated with specially selected, top quality components, AccuCool 3070 produces a clear micro-emulsion in all types of makeup water and contains no nitrites, phenols, diethanolamine, chlorine, or heavy metals. It is formulated with a strong rust inhibitor package, and is suitable for usage on both ferrous and non-ferrous metals.

AccuCool 3070 has been designed to function effectively as both a cutting fluid and a grinding coolant. It possesses superior lubricity characteristics and prevents welding of chips to cutting tools. Lubricity performance is achieved with a combination of physical lubrication from mineral oil, extreme pressure lubrication from top quality additives, and the cooling benefits of machining with high water content solutions.

AccuCool 3070 has been shown to be completely non foaming even under extreme pressure/high speed applications.

APPLICATION

AccuCool 3070 is recommended for the machining and grinding of ferrous and non-ferrous alloys. Operations include: milling, turning, drilling, boring, and threading. Also, O.D. and I.D. grinding operations including centerless and surface grinding.

MIXING RATIOS

When used for machining, mixing ratios will vary between 10 to 25 parts water to 1 part AccuCool 3070. For grinding operations, 25 to 35 parts water to 1 part AccuCool 3070 is recommended.

The data in this Product Information sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information set forth herein is furnished free of charge and is based on technical data that **Angler** believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.

ADVANTAGES

- Long coolant sump life
- Resistance to microbiological growth
- Improved tool life
- Better finishes
- Cleaner machines
- Excellent work piece visibility
- Excellent rust protection
- Greater operator acceptance
- Non-Foaming

TYPICAL SPECIFICATIONS

Appearance	Clear Yellow Liquid
Odor	Slight chemical odor
Gravity, API @ 60 F	0.996
Density, lbs/gal @ 60 F	8.31
Sulfur Content	Nil
Chlorine Content	Nil
pH Value, 9% Concentration	9.2

Angler Industries (Division of DuBois Chemicals) • 860-564-0080 • info@anglerindustries.com

The data in this Product Information sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information set forth herein is furnished free of charge and is based on technical data that **Angler** believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.