

AccuCut 2140P

Cutting Oil



Description

AccuCut 2140P is a medium viscosity, sulfur and chlorine free cutting oil. The fat content of this tri-purpose screw machine oil provides excellent finishes.

Key Properties

- Non-sulfurized making it safe for use on yellow metals
- Can be removed by conventional cleaning methods
- Light colored allows the operator to view the parts during machining
- Low odor
- Non-chlorinated which reduces the cost of disposal

Typical Specifications:

TEST	RESULT
Color	Amber
Viscosity @ 100°F (sus) typ	130
Fat	Present
Chlorine	None
Sulfur	None
Flash Point °F (COC) min	350
Lbs per Gallon	7.2

Applications

- Screw machining
- Honing, tapping, threading
- Contact your sales representative for other application information

Material Compatibility

AccuCut 2140P is recommended for use on all metals, including steel, brass, copper and aluminum.

Safe Handling and Storage Instructions

Before handling and using, the Safety Data Sheet (SDS) should be read and understood by all personnel in contact with this product. General indoor storage at room temperature is recommended.

Disposal

Any disposal of this product should be in compliance with all federal, state and local regulations. Please refer to the Safety Data Sheet (SDS) for instructions regarding proper disposal of this product.

Precautions

Please refer to the label and Safety Data Sheet for all warnings, recommendations for safety equipment, and other regulatory information. Copies of the Safety Data Sheet (SDS) can be ordered by calling 800-438-2647.

This information is presented in good faith, but no warranty, expressed or implied is given. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. This is an uncontrolled copy and changes can be made to this document without notice.