# PRODUCT INFORMATION



#### **ANGLER INDUSTRIES, INC.**

61 Industrial Park Rd • PO Box 217 Sterling, CT 06377 860-564-0080 • FAX 860-564-3598





## AccuDraw 5053

## Heavy Duty Stamping and Drawing Fluid

## **DESCRIPTION**

**AccuDraw 5053** is a clear, yellow colored oil of heavy medium viscosity. It contains stain suppressed chlorinated paraffins which provide the chemical extreme pressure barrier necessary for the flow of drawn metal over die surfaces without rupture of the lubricant film. This type of protection extends die life and promotes production of uniform work pieces with surfaces free of score marks.

## **APPLICATION**

**AccuDraw 5053** should be used as received for stamping and drawing applications. It may be applied to blanks or strips by spray, brush or wiper pads. Parts cleaning is easily accomplished with vapor degreasing, petroleum or chlorinated solvent dip, or with a hot alkaline wash.

## **TYPICAL SPECIFICATIONS**

Density @ 60°F, lbs/gal	9.21
Color, ASTM	2
Viscosity SUS @ 100°F	266
Chlorine, % wt.	27.75
Flash Point, °F	330
Copper Strip Corrosion	1a

The data in this Product Information sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information set forth herein is furnished free of charge and is based on technical data that **Angler** believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.