

Perkote 40-262

Rust Preventive

Description:

Perkote 40-262 is an outstanding water displacing, non-emulsifiable, non-staining, thin film rust preventive. Ideal for in process or final protection where coolants, water, alkaline cleaner or high humidity are present.

Features:

- Polar additives provide exceptional water displacing characteristics
- Humidity test panels exceed 30 days protection, which indicates indoor storage protection in excess of 1 year
- Black stain inhibitor prevents black metal to metal contact stain
- Easily applied by dipping, spraying or brushing
- Readily removed with conventional cleaning methods

Typical Specifications:

<u>TEST</u>	<u>RESULT</u>
ASTM, Color	Light Amber
Barium	Present
Calcium	None
Viscosity at 100°F (sus)	40
Film Type	Light Oil
Flash Point °F (coc)	265
Lbs per Gallon	7.0

Safe Handling and Storage Instructions

Before handling and using, the Safety Data Sheet (SDS) should be read and understood by all personnel in contact with this product.

Disposal

Any disposal of this product should be in compliance with all federal, state and local regulations. Please refer to the Safety Data Sheet (SDS) for instructions regarding proper disposal of this product.

Precautions

KEEP OUT OF THE REACH OF CHILDREN.

Please refer to the label and Safety Data Sheet for all warnings, recommendations for safety equipment, and other regulatory information. Copies of the Safety Data Sheet (SDS) can be ordered by calling 800-438-2647.

This information is presented in good faith, but no warranty, expressed or implied is given. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. This is an uncontrolled copy and changes can be made to this document without notice.